



➤ **Hollow Rotary Disk Pumps**



Technical Features	
ND pipes (mm)	From 25 to 200
Flow rate (m3/h)	From 0,3 to 210
Design pressures (bar)	10
Max. temperature (°C)	280
Rotation speed (RPM)	From 0 to 500
Viscosity (cSt.)	From 1 to 200.000

➤ **Rotary Vane Pumps**



Technical Features	
ND pipes (mm)	From 32 to 100
Flow rate (m3/h)	From 2,4 to 115
Design pressures (bar)	10
Max. temperature (°C)	70
Rotation speed (RPM)	From 300 to 1.450
Viscosity (cSt.)	From 0,5 to 1.100

➤ **Twin Screw Pumps and Multiphase Pumps**



Technical Features	
ND pipes (mm)	From 35 to 750
Flow rate (m3/h)	From 0,5 to 5.000
Design pressures (bar)	Diff. Pressure up to 60 bar
Max. temperature (°C)	350
Rotation speed (RPM)	From 0 to 3.600
Viscosity (cSt.)	0,5 - 200.000

➤ **Cryogenic Pumps & Skids**



Main Features	
Operating Pressure	From 30 to 350 Barg
Flow rates (l/min)	3-16 9-48
Temperature Range (°C)	-270° > 70°
Rotation speed (RPM)	100 - 400

➤ **Packaged Systems & Skids**



Applications	
Chemical injection systems	
Fuel & Gas skids	
Integrated skids	
Nitrogen generators	
Methanol injection systems	
Pipeline Manifold Packaged Systems	
Subsea Chemical Injection Packages	
Reverse Osmosis Skid	